Forum: CentOS 5 - Server Support
Topic: cron and sendmail
Subject: Re: cron and sendmail
Posted by: RENOO
Posted on: 2010/8/8 16:10:56

Thank you once again.

Not I didn't not modify anything in my sendmail configuration before.

Now, as you mentionned, I modified my /etc/mail/sendmail.mc and wrote
dnl define(`SMART_HOST', `smtp.free.fr')dnl

It seems the command make went well :

[root@rio ~]# make -C /etc/mail make: Entering directory `/etc/mail' make: Leaving directory `/etc/mail'

But still when I tried to send a mail :
Ocean@rio:~$ echo hello | mail -s test rlaxxx@yahoo.fr
(I have changed the outgoing adress this time)

[root@rio ~]# mailq /var/spool/mqueue (1 request) -----Q-ID----- --Size-- -----Q-Time----- ----------Sender/Recipient---------- o78Fo4HS016111 6 Sun Aug 8 17:50 <Ocean@localhost.localdomain> (host map: lookup (yahoo.fr): deferred) <rlaxxx@yahoo.fr> Total requests: 1

the mail do not leave the queue.

I had a look at the following page :

map lookup

I don't understand everything but I can run the following command (see at the end of the page)

sendmail -v -d8.32 -qIo78Fo4HS016111 Running /var/spool/mqueue/o78Fo4HS016111 (sequence 1 of 1) dns_getcanonname(yahoo.fr, trymx=1) dns_getcanonname: trying yahoo.fr. (AAAA) NO: errno=0, h_errno=4 dns_getcanonname: trying yahoo.fr. (A) YES dns_getcanonname: yahoo.fr getmxrr(yahoo.fr., droplocalhost=1) <rlaborbe@yahoo.fr>... Connecting to mx2.mail.eu.yahoo.com. via esmtp... 220 mta1013.mail.ukl.yahoo.com ESMTP YSmtp service ready >>> EHLO localhost.localdomain 250-mta1013.mail.ukl.yahoo.com 250-8BITMIME 250-SIZE 41943040 250 PIPELINING >>> MAIL From:<Ocean@localhost.localdomain> SIZE=564 250 sender <ocean@localhost.localdomain> ok >>> RCPT To:<rlaxxx@yahoo.fr> >>> DATA 250 recipient <rlaxxx@yahoo.fr> ok 354 go ahead >>> . 250 ok dirdel <rlaxxx@yahoo.fr>... Sent (ok dirdel)

Closing connection to mx2.mail.eu.yahoo.com. >>> QUIT 221 mta1013.mail.ukl.yahoo.com

And the mail arrives at destination. Great !
Does this help ?