Forum: CentOS 5 - Server Support
Topic: cron and sendmail
Subject: Re: cron and sendmail
Posted by: RENOO
Posted on: 2010/8/10 18:09:39

The weekend is over now.

I still playing with mails !! I have notice view things :

I have several users and this machine. One is "Ocean", another is "tux", and the third one is "ren"

"ren" and "tux" can send mail to each other easily with the command from "ren" session

echo "Hi tux" | mail -s Subjet ren

But the user Ocean has trouble and I have read it is because of the capital O.
" User Unknow" appears (mail -v -s)

So the User Unknow error in the previous code comes from the capital O.

Now from ren session

echo "Hello free" | mail -v -s subject rlaxxx@free.fr rlaxxx@free.fr... Connecting to [127.0.0.1] via relay... 220 localhost.localdomain ESMTP Sendmail 8.13.8/8.13.8; Tue, 10 Aug 2010 20:02:42 +0200 >>> EHLO localhost.localdomain 250-localhost.localdomain Hello localhost.localdomain [127.0.0.1], pleased to meet you 250-ENHANCEDSTATUSCODES 250-PIPELINING 250-8BITMIME 250-SIZE 250-DSN 250-ETRN 250-AUTH DIGEST-MD5 CRAM-MD5 250-DELIVERBY 250 HELP >>> MAIL From:<ren@localhost.localdomain> SIZE=50 AUTH=ren@localhost.localdomain 250 2.1.0 <ren@localhost.localdomain>... Sender ok >>> RCPT To:<rlaxxx@free.fr> >>> DATA 250 2.1.5 <rlaxxxx@free.fr>... Recipient ok (will queue) 354 Enter mail, end with "." on a line by itself >>> . 250 2.0.0 o7AI2gbv006479 Message accepted for delivery rlaborbe@free.fr... Sent (o7AI2gbv006479 Message accepted for delivery) Closing connection to [127.0.0.1] >>> QUIT 221 2.0.0 localhost.localdomain closing connection

The mail is queue but not send
mailq /var/spool/mqueue (1 request) -----Q-ID----- --Size-- -----Q-Time-----
----------Sender/Recipient---------- o7AI2gbv006479 11 Tue Aug 10 20:02
<ren@localhost.localdomain> (host map: lookup (free.fr): deferred)
  <rlaxxx@free.fr> Total requests: 1
May I ask for help ?