Forum: CentOS 6 - General Support
Topic: iptables blocks dns
Subject: Re: iptables blocks dns
Posted by: agriz
Posted on: 2011/12/8 22:53:08

iptables -F iptables -P INPUT DROP iptables -P FORWARD DROP iptables -P OUTPUT DROP //output settings iptables -A OUTPUT -o lo -j ACCEPT iptables -A OUTPUT -o eth0 -m state --state RELATED,ESTABLISHED -j ACCEPT iptables -A OUTPUT -o eth0 -p tcp -m state --state NEW -m tcp --dport 80 -j ACCEPT iptables -A OUTPUT -o eth0 -p tcp -m state --state NEW -m tcp --dport 443 -j ACCEPT iptables -A OUTPUT -o eth0 -p tcp -m state --state NEW -m tcp --dport 25 -j ACCEPT iptables -A OUTPUT -o eth0 -p tcp -m state --state NEW -m tcp --dport 10000 -j ACCEPT //input settings iptables -A INPUT -i lo -j ACCEPT iptables -A INPUT -i eth0 -p tcp -m state --state RELATED,ESTABLISHED -j ACCEPT iptables -A INPUT -i eth0 -p tcp -m state --state NEW -m tcp --dport 80 -j ACCEPT iptables -A INPUT -i eth0 -p tcp -m state --state NEW -m tcp --dport 443 -j ACCEPT iptables -A INPUT -i eth0 -p tcp -m state --state NEW -m tcp --dport 25 -j ACCEPT iptables -A INPUT -i eth0 -p tcp -m state --state NEW -m tcp --dport 10000 -j ACCEPT //ssh settings iptables -A INPUT -i eth0 -p tcp -m state --state NEW -m tcp --dport 1234 -j ACCEPT

Yes, I have the following service running in server httpd, sendmail, webmin, https, mysqld

Now i have made changes in input settings.
Do i need to create new state for every output port?

will the above settings allow curl other sites with port 80, yum and wget?